

NativeSPTCPListener

The <TCPListener> element provides a remoting layer based on a TCP socket and is recommended for use on Windows.

Version 2.4 and above default to this option when the element is omitted on Windows platforms.

```
<TCPListener address="127.0.0.1" port="1600" acl="127.0.0.1"/>
```

Attributes

- `address` (IP address in decimal dotted notation) (default is 127.0.0.1 on V2.4+)
 - Network address to bind or connect to.
- `port` (integer) (default is 1600 on V2.4+)
 - TCP socket port to bind or connect to.
- `acl` (space-delimited list of IP addresses in decimal dotted notation) (default is 127.0.0.1)
 - List of network addresses to permit connections from. As of V2.5, use of CIDR notation and IPV6 addresses and ranges is supported.
- `stackSize` (size in kilobytes) (defaults to 0) ([Version 2.4 and Above](#))
 - If non-zero, sets the stack size of worker threads in kilobytes. Zero results in the default OS-supplied size being used.
- `clientAddress` (IP address in decimal dotted notation) ([Version 2.6 and Above](#))
 - If set, this overrides the `address` attribute for the "in-process" half of the system (web server modules).
- `clientPort` (integer) ([Version 2.6 and Above](#))
 - If set, this overrides the `port` attribute for the "in-process" half of the system (web server modules).